

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
3 March 2005 (03.03.2005)


PCT

(10) International Publication Number  
**WO 2005/019679 A1**

- (51) International Patent Classification<sup>7</sup>: **F16D 65/54**, (74) Agent: **BULSON, Don, W.**; Renner, Otto, Boisselle & Sklar, LLP, 1621 Euclid Avenue -19th Floor, Cleveland, OH 44115 (US).
- (21) International Application Number: PCT/US2004/026850
- (22) International Filing Date: 18 August 2004 (18.08.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/495,990 18 August 2003 (18.08.2003) US
- (71) Applicant (for all designated States except US): **GOODRICH CORPORATION** [US/US]; Four Coliseum Centre, 2730 West Tyvola Road, Charlotte, NC 28217-4578 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **SOELLNER, Kenneth, A.** [US/US]; c/o Goodrich Corporation, 101 Waco Street, Troy, OH 45373 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: BRAKE ADJUSTING MECHANISM



(57) Abstract: An adjuster assembly (48) for automatically maintaining a uniform release clearance (and therefore a uniform stroke) for brakes and similar equipment. The adjuster assembly (48) comprises a continuous tube (62) and an expansion member (58) together having a combined length controlling the release clearance of selectively engageable friction parts. The expansion member (58) has an expansion device frictionally engaging the interior of the continuous tube (62) to effect progressive circumferential expansion of the continuous tube (62) when the expansion device is axially drawn through the continuous tube to compensate for wear of the friction parts during actuation and release of said selectively engageable parts. Unlike prior art adjuster assemblies, the continuous tube (62) advantageously has an end portion (70) processed differently from the balance of the continuous tube (62) for extending the usable portion of the continuous tube.



**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*